

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

THIS PAGE BLANK (USPTO)

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 094 018 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
25.04.2001 Bulletin 2001/17

(51) Int. Cl.⁷: **B65G 17/00**, B65G 17/46,
B65G 47/08, B65G 17/08

(21) Application number: 00203376.9

(22) Date of filing: 28.09.2000

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

• De Gooyer, Gerrit
3905 MG Veenendaal (NL)
• Scholten, Gerrit Jan
6991 ZT Rheden (NL)

(30) Priority: 18.10.1999 NL 1013333

(71) Applicant: EBM TECHNIEK B.V.
3925 CK Scherpenzeel (NL)

(74) Representative:
Prins, Hendrik Willem et al
Arnold & Siedsma,
Advocaten en Octrooigemachtigden,
Sweelinckplein 1
2517 GK Den Haag (NL)


(72) Inventors:
• Rijkse, Rijk
8075 PH Elspeet (NL)

(54) Transport assembly

(57) The invention relates to a transport assembly for transporting objects, which assembly comprises:

- a chain conveyor comprising mutually coupled links;
- at least one carrier placeable on the chain conveyor, on which carrier objects can be placed and which is slidable relative to the chain; and

- guide means for guiding carriers placed on the chain such that the sliding movement transversely of the transporting movement is bounded, wherein the guide means are arranged on the chain conveyor.



EP 1 094 018 A1

Description

[0001] The invention relates to a transport assembly for transporting objects, which assembly comprises:

- a chain conveyor comprising mutually coupled links;
- at least one carrier placeable on the chain conveyor, on which carrier objects can be placed and which is slidable relative to the chain; and
- guide means for guiding carriers placed on the chain such that the sliding movement transversely of the transporting movement is bounded.

[0002] Such transport assemblies are generally known. Carriers are transported herewith past different stations and the carriers are temporarily stopped at a station, for instance to place objects on the carrier. While the carrier is stopped the chain conveyor continues to run, so that other carriers placed on the chain are transported further. In order to prevent the carriers falling from the chain conveyor, guide rails are arranged on either side of the chain in known transport assemblies.

[0003] The drawback of the above stated transport assemblies is that the width of a carrier and the objects placed thereon is limited by the distance between the guide rails.

[0004] The guide rails have the further drawback that they limit the access to the carriers from the side.

[0005] In addition, the arranging of the guide rails requires extra time during the manufacture of such a transport assembly.

[0006] It is an object of the present invention to obviate the above stated drawbacks.

[0007] This objective is achieved with a transport assembly according to the invention which is characterized in that the guide means are arranged on the chain conveyor.

[0008] By arranging the guide means on the chain conveyor a free lateral access to the carriers is obtained and the width of the carriers is no longer limited by guide rails arranged along the chain conveyor.

[0009] According to a preferred embodiment according to the invention the guide means comprise a guide rib, wherein the guide rib extends in the transporting direction of the chain, and the at least one carrier comprises a slot extending along the length of the carrier such that when a carrier is placed on the chain the guide rib extends into the slot.

[0010] This guide rib ensures that a carrier placed on the chain can slide in the transport direction but not transversely thereof. The guide rib can be manufactured from a flexible material.

[0011] According to a further embodiment according to the invention, each link comprises a rib such that the ribs of mutually coupled links form the guide rib.

[0012] The rib of each link herein preferably comprises a recess on a first side and a narrowed portion on

an opposite second side such that the narrowed portion extends into the recess of a rib of an adjoining link.

[0013] The formed guide rib hereby remains continuous and no gaps occur in the guide rib during pivoting of the chain, for instance round a chain wheel.

[0014] According to another embodiment according to the invention the guide means comprise a slot extending in the transport direction of the chain over the whole length of the chain, and the at least one carrier comprises a rib co-acting with the slot.

[0015] According to yet another embodiment according to the invention the guide means comprise two guide surfaces arranged on either side of each link and the at least one carrier comprises a slot extending along the length and engaging round the guide surfaces, the width of which slot is greater than the distance between the guide surfaces.

[0016] These and other features will be further elucidated with reference to the annexed drawings.

Figure 1 shows a perspective view of a first embodiment of the invention.

Figure 2 shows a first detail of the embodiment of figure 1 in perspective view.

Figure 3 shows a second detail of the embodiment of figure 1 in perspective view and with partly cut-away parts.

Figures 4 and 5 show a perspective view of a link of the embodiment according to figure 1.

Figure 6 is a perspective view of a second embodiment according to the invention.

Figure 7 is a perspective view of a third embodiment according to the invention.

[0017] Figure 1 shows a first embodiment of a transport assembly 1 according to the invention. This assembly 1 has a chain conveyor 2 which is guided along chain wheels 3, 4. A carrier 5 is placed on chain conveyor 2.

[0018] Chain conveyor 2 is constructed from a large number of mutually coupled links 6 (see also figures 2 and 3). Each link comprises a sliding surface 7 on which is arranged a rib 8. Rib 8 co-acts with a slot 9 arranged in the bottom surface of carrier 5. The bottom surface of carrier 5 lies on the sliding surfaces 7 of the links.

[0019] Recesses 10 are arranged in the side of carrier 5. An actuatable protrusion 11 can be placed in these recesses 10 to enable stopping of a carrier 5 while chain conveyor 2 continues to run (see figure 3). The underside of carrier 5 herein then slides over the sliding surfaces 7 of the links, while ribs 8 prevent carrier 5 from being able to displace in a direction transversely of the transport direction.

[0020] The slot 9 arranged in carrier 5 has a cross-sectional form roughly resembling the cross-sectional form of a rugby ball. Due to the curved surfaces 12 of this slot 9 it is possible to transport the carriers 5 through a bend. It is herein even possible to stop the

carrier 5 in a bend.

[0021] Carrier 5 further has a recess 13 in which for instance an iron plug can be placed, so that the position of a carrier can be determined with detection means 14.

[0022] Chain conveyor 2 can preferably pivot on two mutually perpendicular axes X, Y (see figure 4), so that the chain can bend in horizontal and vertical planes. For this purpose the links are formed as follows.

[0023] In addition to the sliding surface 7 with rib 8 thereon, each link 6 has a fork-like part 14 on the underside of the sliding surface. This part 14 is provided on the one side with two shaft stubs 15 and on the other side with two recesses 16 (see figures 4 and 5). In the coupled situation the shaft stubs 15 of a link 6 engage in the recesses 16 of a following link. Fork-like part 14 is formed such that when links are coupled there is space left over, whereby the teeth 17 of for instance toothed wheel 3 can engage herein and whereby the chain conveyor 2 formed by links 6 can be driven.

[0024] In order to enable pivoting of links 6 round axis X, so that chain 2 can rotate out of its plane in two directions, the rib 8 also has a fork shape. The two legs 18 of rib 8 engage round the single part 19 of an adjoining link, so that a continuous ridge is formed on chain conveyor 2. Legs 18 are herein rounded off, so that the continuous ridge is maintained during a pivoting movement of link 6 round axis X.

[0025] The sliding surfaces 7 of link 6 have chamfers 20, and recesses 16 are slightly larger than shaft stubs 15, whereby the link can also pivot round axis Y.

[0026] Figure 6 shows a second embodiment of the invention. This embodiment comprises a link chain 30, wherein each link 31 comprises a rib 32. On this link chain 30 can be placed a carrier 33 which protrudes on either side of chain 30. Arranged on the underside of carrier 33 are protrusions 34 which engage round ribs 32, whereby the carrier is guided and supported on the chain. A slot as shown in the foregoing embodiment can also be applied instead of these protrusions 34.

[0027] It is also possible in this embodiment to make the distance between protrusions 34 such that they extend on either side of the links 31, whereby links 31 themselves provide the guiding of carrier 33. The ribs 32 on links 31 are then unnecessary.

[0028] Figure 7 shows a third embodiment. This embodiment likewise comprises a link chain 40 and a carrier 41 placeable thereon. Each link 42 is provided on the top with a slot 43 extending over the length. Protrusions 44 arranged on the underside of carrier 41 fall into this slot.

- at least one carrier placeable on the chain conveyor, on which carrier objects can be placed and which is slidable relative to the chain; and
- guide means for guiding carriers placed on the chain such that the sliding movement transversely of the transporting movement is bounded,

characterized in that

the guide means are arranged on the chain conveyor.

2. Transport assembly as claimed in claim 1, **characterized in that**

the guide means comprise a guide rib, wherein the guide rib extends in the transporting direction of the chain, and that the at least one carrier comprises a slot extending along the length of the carrier such that when a carrier is placed on the chain the guide rib extends into the slot.

3. Transport assembly as claimed in claim 2, **characterized in that**

each link comprises a rib such that the ribs of mutually coupled links form the guide rib.

4. Transport assembly as claimed in claim 3, **characterized in that**

the rib of each link comprises a recess on a first side and a narrowed portion on an opposite second side such that the narrowed portion extends into the recess of a rib of an adjoining link.

5. Transport assembly as claimed in claim 1, **characterized in that**

the guide means comprise a slot extending in the transport direction of the chain over the whole length of the chain, and that the at least one carrier comprises a rib co-acting with the slot.

6. Transport assembly as claimed in claim 1, **characterized in that**

the guide means comprise two guide surfaces arranged on either side of each link and that the at least one carrier comprises a slot extending along the length and engaging round the guide surfaces, the width of which slot is greater than the distance between the guide surfaces.

Claims

1. Transport assembly for transporting objects, which assembly comprises:

- a chain conveyor comprising mutually coupled links;








FIG. 1









European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 20 3376

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IntCl.7)
A	FR 2 776 641 A (ERMES AUTOMATION) 1 October 1999 (1999-10-01) * claim 1; figures *	1-6	B65G17/00 B65G17/46 B65G47/08 B65G17/08
A	WO 97 42109 A (BOS KUIL DRE ROELF DE ;SCHOLTEN GERRIT JAN (NL); VISSCHER FRANK RO) 13 November 1997 (1997-11-13) * page 6, line 19 - page 7, line 13; figures *	1	
			TECHNICAL FIELDS SEARCHED (IntCl.7)
			B65G B23Q
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 16 January 2001	Examiner Ostyn, T
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons</p> <p>& : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03 82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 20 3376

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

16-01-2001

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
FR 2776641	A	01-10-1999	NONE	
WO 9742109	A	13-11-1997	NL 1003035 C	07-11-1997
			CA 2252949 A	13-11-1997
			EP 1030812 A	30-08-2000

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

THIS PAGE BLANK (USPTO)